



BR 鋰氟化石墨扣式電池

型號	標稱電壓 (V)	標稱容量 (mAh)	標準放電條件 (KΩ)	工作溫度 (°C)	最大尺寸 (mm)	重量 (g)
BR1225	3	50	30	φ 12.5×2.5	-40~85	0.8
BR1632	3	130	15	φ 16.0×3.2	-40~85	1.7
BR2016	3	60	30	φ 20.0×1.6	-40~85	1.6
BR2025	3	130	15	φ 20.0×2.5	-40~+85	2.4
BR2032	3	200	15	φ 20.0×3.2	-40~+85	2.9
BR2325	3	165	15	φ 23.0×2.5	-40~+85	3.2
BR2330	3	260	15	φ 23.0×3.0	-40~+85	3.5
BR2335	3	300	15	φ 23.0×3.5	-20~+60	4.3
BR2354	3	420	7.5	φ 23.0×5.4	-40~+85	6.2
BR2430	3	230	15	φ 24.5×3.0	-40~+85	4.2
BR2450	3	550	7.5	φ 24.5×5.0	-40~+85	6
BR2477	3	800	4.7	φ 24.5×7.7	-40~+85	9.6
BR3032	3	500	7.5	φ 30.0×3.2	-40~+85	5.5